

IV Workshop de Computação Quântica - UFSC

QAOA Algorithm

Otto Menegasso Pires
otto28mai@gmail.com

25/10/2021



UNIVERSIDADE FEDERAL
DE SANTA CATARINA



Variational Quantum Algorithms

Variational Quantum Algorithms (VQAs) are a class of hybrid quantum-classical algorithms that employ a classical optimizer to train a parametrized quantum circuit and provide a general framework that can be used to solve a wide array of problems.

VQAs emerged as the leading strategy to obtain quantum advantage on NISQ devices.

Variational Quantum Algorithms




Figure: Schematic diagram of a Variational Quantum Algorithm (VQA).

- **Quantum Approximate Optimization Algorithm:** in its first publication by Farhi et al [FGG14] the QAOA was an approximate optimization algorithm, whose behaviour was based in the alternated application of a Hamiltonian based in a cost function and a Mixing Hamiltonian.
- **Quantum Alternating Operator Ansatz:** the QAOA framework was later expanded by Hadfield et al [HWO⁺19] so that it would allow families of more general operators.

QAOA Circuit

$$H_P \Rightarrow e^{-i\gamma H_P} = \text{---} \boxed{U_P(\gamma)} \text{---}$$

$$H_M \Rightarrow e^{-i\beta H_M} = \text{---} \boxed{U_M(\beta)} \text{---}$$

$$QAOA_p(\beta, \gamma) = U_M(\beta_p)U_P(\gamma_p) \dots U_M(\beta_1)U_P(\gamma_1)$$

$$|\beta, \gamma\rangle = QAOA_p(\beta, \gamma) |s\rangle$$





Figure: QAOA quantum circuit


Initial State

Design criteria: The initial state must be feasible and *trivial*, $O(1)$ or $O(\log n)$, to implement

$|+\dots+\rangle$ -state $O(1)$




Feasible State $O(1)$



Initial State


W-state $O(\log n)$



3-Qubit W-state: $|100\rangle + |010\rangle + |001\rangle$


Phase separation operator

Design criteria: We require the family of phase separation operators $U_P(\gamma)$ to be diagonal in the computational basis. Most of the time the operator will take the form $U_P(\gamma) = e^{-i\gamma H_P}$, where H_P is the Problem Hamiltonian of the classic objective function f .



Mixing Unitaries (Mixers)

Design criteria: The mixing operators must preserve feasible space and explore the feasible space.



- *X-Mixer*: $H_M = \sum_j X_j$

$$U_M(\beta) = e^{-i\beta H_M} = \prod_j e^{-i\beta X_j}$$

- *XY-Mixer*: $H_M = \sum_{i,j} X_i X_j + Y_i Y_j$

$$U_M(\beta) = e^{-i\beta H_M} = \prod_{i,j} e^{-i\beta X_i X_j + Y_i Y_j}$$

The expectation value $\langle x | H_P | x \rangle$ of the problem Hamiltonian is estimated by taking the average of the states obtained by the measurements.

$$\langle x | H_P | x \rangle \equiv f(x)$$

The expectation value is then optimized using a classical optimization method over the $2p$ parameters γ and β .

QAOA Classical part

- Off-the-shelf gradient-free [WHT16, MW19, AASG20]
- Off-the-shelf gradient-based [VGS⁺20, ZWC⁺20, MC21]
- Deep Reinforcement Learning [KSC⁺20]
- Metalearning [YWZ⁺21]

A recent study [FPCV⁺21] showed that some algorithms which have great performance with QAOA are Adam, Conjugate Gradient, COBYLA, Nelder-Mead, Powell and SPSA.

Practical Example - MaxCut

References I

-  Mahabubul Alam, Abdullah Ash-Saki, and Swaroop Ghosh. Accelerating quantum approximate optimization algorithm using machine learning. In *2020 Design, Automation Test in Europe Conference Exhibition (DATE)*, pages 686–689, 2020.
-  Edward Farhi, Jeffrey Goldstone, and Sam Gutmann. A quantum approximate optimization algorithm, 2014.
-  Mario Fernández-Pendás, Elías F. Combarro, Sofia Vallecorsa, José Ranilla, and Ignacio F. Rúa. A study of the performance of classical minimizers in the quantum approximate optimization algorithm. *Journal of Computational and Applied Mathematics*, page 113388, 2021.

References II



Stuart Hadfield, Zihui Wang, Bryan O’Gorman, Eleanor Rieffel, Davide Venturelli, and Rupak Biswas.

From the quantum approximate optimization algorithm to a quantum alternating operator ansatz.

Algorithms, 12(2):34, 2 2019.



Sami Khairy, Ruslan Shaydulin, Lukasz Cincio, Yuri Alexeev, and Prasanna Balaprakash.

Learning to optimize variational quantum circuits to solve combinatorial problems.

Proceedings of the AAAI Conference on Artificial Intelligence, 34(03):2367–2375, Apr. 2020.

References III

-  [Matija Medvidović and Giuseppe Carleo.](#)
Classical variational simulation of the quantum approximate optimization algorithm.
npj Quantum Information, 7:101, Jun 2021.
-  [S. Marsh and J. B. Wang.](#)
A quantum walk-assisted approximate algorithm for bounded np optimisation problems.
Quantum Information Processing, 18:61, 1 2019.
-  [Pontus Vikstål, Mattias Grönkvist, Marika Svensson, Martin Andersson, Göran Johansson, and Giulia Ferrini.](#)
Applying the quantum approximate optimization algorithm to the tail-assignment problem.
Phys. Rev. Applied, 14:034009, Sep 2020.

References IV

-  Dave Wecker, Matthew B. Hastings, and Matthias Troyer.
Training a quantum optimizer.
Phys. Rev. A, 94:022309, Aug 2016.
-  Gonglin Yuan, Haibin Wang, Jiaojiao Zhao, Bosi Wang, and Lian Tong.
A quantum approximate optimization algorithm with
metalearning for maxcut problem and its simulation via
tensorflow quantum.
Mathematical Problems in Engineering, 2021:6655455, 3 2021.

References V



Leo Zhou, Sheng-Tao Wang, Soonwon Choi, Hannes Pichler, and Mikhail D. Lukin.

Quantum approximate optimization algorithm: Performance, mechanism, and implementation on near-term devices.

Phys. Rev. X, 10:021067, Jun 2020.